



MICROSTONE®
BY MICROFORCE

INNIFLOOR


SELF-LEVELLING
FLOOR SCREED 3-60 MM

SELF-LEVELLING
FAST DRYING
3-60 MM
FOOT TRAFFIC

25KG

- SELFLEVELLING
- FAST DRYING
- 3-60 MM
- FOOT TRAFFIC
- A1 FIRE RATED
- COLOUR OPTIONS
- UNDERFLOOR HEATING
- INTERIOR EXTERIOR

COLOUR OPTIONS - 8 SHADES



BLANCO

GRIS PASTEL

GRIS PALE

GRIS LAVA

GRIS CEMENTO

NEGRO

GRIS NOCHE

VERDE CLARO

INNIFLOOR

SELF-LEVELLING FLOOR
SCREED 3-60 MM

MICROSTONE®
BY MICROFORCE

DESCRIPTION

Innifloor is a fibre-reinforced, self-levelling cement screed for repairing, levelling and building up floors from 3 to 60 mm, in new builds and renovations. It sets fast — walkable in 8 hours — and gives a strong, flat base ready for microcement, tiles, wood, vinyl or carpet.

KEY FEATURES

- Self-levelling from 3 to 60 mm
- Foot traffic after 8 hours
- Compressive strength > 50 N/mm² (28 days)
- Suitable for underfloor heating from 30 mm
- Floating screed over plastic or impact sheet from 3 cm
- Ready for microcement, tiles, wood, parquet, vinyl

TECHNICAL INFORMATION

PRODUCT TYPE

Self-levelling cement screed

COMPOSITION

Cement, quartz sand, fibres, mineral additives

THICKNESS

3-60 mm

CONSUMPTION

14 kg/m² per cm of thickness

MIXING WATER

5.0-6.25 L per 25 kg bag

POT LIFE

25-30 minutes

TOUCH DRY

4-5 hours

FOOT TRAFFIC

> 8 hours



COVERAGE

Per 25 kg bag

6m²

at 3 mm

1.8 m² at 10 mm

0.6 m² at 30 mm

APPLICATION



MIXER



POUR



SPIKE ROLL

PACKAGING



25KG

Bag - pallet of 48



PROFESSIONAL PERFORMANCE

Engineered for strength, adhesion and durability.



LOW VOC

Safe for installers and the environment.



WATERPROOF

Reliable protection in wet areas.



PREMIUM QUALITY

Developed for the most demanding projects.

MICROSTONE®
BY MICROFORCE

microstone.co.uk