



-  **A+B** TWO COMPONENT
-  **HIGH HARDNESS**
-  **FOOT TRAFFIC**
-  **HIGH ADHESION**
-  **STAIN RESISTANT**
-  **INTERIOR EXTERIOR**
-  **SEAMLESS FINISH**
-  **EXCELLENT WORKABILITY**

MICREX BASE

WATER-BASED DECORATIVE
& INDUSTRIAL MORTAR

MICROSTONE®
BY MICROFORCE

DESCRIPTION

Micrex Base is a three-component, water-based decorative and industrial mortar. It is the base coat of the Micrex system and can also be used alone as a trowelled-effect coloured coating for floors and walls, inside or out.

KEY FEATURES

- Base coat for Micrex and Micrex Rustik
- Excellent adhesion to resin coatings (> 2 N/mm² to...
- Excellent mechanical and abrasion resistance
- Excellent UV and weather resistance
- Interior and exterior floors and walls
- Tintable with 3-10% water-based colourant

TECHNICAL INFORMATION

PRODUCT TYPE

Three-component water-based mortar (A+B+C)

MIXING RATIO

A 100 : B 50 : C 100

CONSUMPTION

0.3-1 kg/m² per coat, depending on aggregate size

POT LIFE (25°C)

> 2 hours

TOUCH DRY (25°C)

8-10 hours

FOOT TRAFFIC

> 24 hours (25°C)

ADHESION TO CONCRETE

> 2 N/mm²

DENSITY

1.80 ± 0.05 g/ml



HOW IT'S APPLIED

- 1 Prepare** — concrete sound, dry, level and absorbent, cured >28 days, minimum 25 N/mm² compressive and 15 N/mm² tensile strength.
- 2 Mix** — pour B into A, mix at low speed for at least 1 minute, then add C and remix.
- 3 Apply** — steel or rubber trowel at approx. 0.3-0.5 kg/m² per coat.

COVERAGE

Approximately
25-83m²
per coat per 25 kg pack
(depending on aggregate)

APPLICATION



MIXER



TROWEL



BASE COAT

PACKAGING



25KG
Pack A+B+C



PROFESSIONAL PERFORMANCE

Engineered for strength, adhesion and durability.



LOW VOC

Safe for installers and the environment.



WATERPROOF

Reliable protection in wet areas.



PREMIUM QUALITY

Developed for the most demanding projects.

MICROSTONE®

BY MICROFORCE

microstone.co.uk