



-  PROTECTS
-  WATER BASED
-  SATIN FINISH
-  READY TO USE
-  LOW VOC
-  INTERIOR EXTERIOR
-  FAST DRYING
-  EXCELLENT WORKABILITY

ACRYSEAL

ACRYLIC SEALER FOR
MICROCEMENT & POROUS FLOORS

MICROSTONE[®]
BY MICROFORCE

DESCRIPTION

Acryseal is an acrylic sealer for microcement and very porous cement floors. It locks in dust, protects against stains and stands up to heavy traffic, and it is the first seal coat in the Microforce RTU system before the Aquamax topcoat.

KEY FEATURES

- For microcement and very porous floors
- Anti-dust and anti-stain
- Resistant to heavy traffic
- 0.00% VOC
- Ready to use

TECHNICAL INFORMATION

PRODUCT TYPE

Acrylic sealer

APPEARANCE

Opaque cream-white liquid

VOC

0.00%

DENSITY

1.018 g/ml

DRY RESIDUE

21 ± 1%

PH

7.7 ± 0.5

BETWEEN COATS

Approx. 45 minutes



HOW IT'S APPLIED

- 1 Prepare** — remove all emulsion residues and saltpetre.
- 2 First coat** — diluted 50% with water to impregnate.
- 3 Second coat** — neat, after about 45 minutes.
- 4 Finish** — topcoat with Aquamax or maintain with Microwax.

COVERAGE

Coverage

Ask us

for a quantity
first coat diluted 50%

APPLICATION



BRUSH



ROLLER



TWO COATS

PACKAGING



5L
Plastic bottle



PROFESSIONAL PERFORMANCE

Engineered for strength,
adhesion and durability.



LOW VOC

Safe for installers
and the environment.



WATERPROOF

Reliable protection
in wet areas.



PREMIUM QUALITY

Developed for the most
demanding projects.

MICROSTONE[®]
BY MICROFORCE

microstone.co.uk