



READY TO USE



WATER BASED



NONYELLOWING



STAIN RESISTANT



SATIN FINISH



INTERIOR EXTERIOR



FAST DRYING



FOOT TRAFFIC

AQUAMAX 1C

ONE-PART WATER-BASED
POLYURETHANE SEALER

MICROSTONE[®]
BY MICROFORCE

DESCRIPTION

Aquamax 1C is a single-component, water-based polyurethane resin with high solids. Open the tin and apply — it seals porous microcement, concrete and terracotta and doubles as a satin topcoat. It is extremely hard yet keeps good elasticity, which helps prevent cracking, and it does not yellow.

KEY FEATURES

- Covers approx. 33 m² per coat per 5 kg
- Single component — no mixing
- Sealer and satin topcoat in one
- Waterproof and water-repellent
- Non-yellowing
- High hardness with high elasticity
- Resistant to wear and foot traffic

TECHNICAL INFORMATION

PRODUCT TYPE

One-component water-based polyurethane resin

CONSUMPTION

150 g/m²

DILUTION

10-20% water

TOUCH DRY (23°C)

45 minutes

FULL DRY

48 hours

FINISH

Satin

APPLICATION TEMPERATURE

15–30°C (do not apply above 25°C on hot surfaces)



HOW IT'S APPLIED

- 1 **Prepare** — surface clean, dry and free of dust and grease.
- 2 **Apply** — by roller in thin, even coats.
- 3 **Second coat** — once the first is touch dry.
- 4 **Cure** — allow 48 hours for full drying before heavy use.

COVERAGE

Approximately
33m²
per coat per 5 kg
06.5 m² per coat
per 1 kg

APPLICATION



ROLLER



BRUSH



TWO COATS

PACKAGING



1KG / 5KG
Plastic bottles



PROFESSIONAL PERFORMANCE

Engineered for strength,
adhesion and durability.



LOW VOC

Safe for installers
and the environment.



WATERPROOF

Reliable protection
in wet areas.



PREMIUM QUALITY

Developed for the most
demanding projects.

MICROSTONE[®]
BY MICROFORCE

microstone.co.uk