



- A+B** TWO COMPONENT
- WATER BASED**
- STAIN RESISTANT**
- NONYELLOWING**
- FOOT TRAFFIC**
- HIGH HARDNESS**
- MATT · SATIN · GLOSS**
- INTERIOR EXTERIOR**

HOW IT'S APPLIED

- 1 Lightly sand a clean, dry, dust-free surface (cement substrates below 4% moisture).
- 2 Pour A and B into one container (5:1), mix thoroughly with a mechanical mixer and rest for 10 minutes.
- 3 Apply by roller, spray or airless without overloading, 45-60 minutes between coats.

AQUAMAX

TWO-PART WATER-BASED
POLYURETHANE VARNISH

MICROSTONE
BY MICROFORCE

DESCRIPTION

Aquamax is the two-component, water-based polyurethane varnish that seals and protects Microforce microcement floors and walls. It is waterproof yet breathable, deepens and enhances colour, resists abrasion and holds less dirt — indoors and out. Choose a matt, satin or gloss finish.

KEY FEATURES

- Two-component water-based polyurethane
- Waterproof and breathable
- Excellent adhesion and high abrasion resistance
- Enhances colour; reduces dirt retention
- Matt, satin or gloss
- Interior and exterior; 7.2 kg covers approx. 70 m²

TECHNICAL INFORMATION

PRODUCT TYPE

Two-component water-based polyurethane varnish

MIXING RATIO

5 parts A : 1 part B

CONSUMPTION

±0.1 kg/m²

POT LIFE

2 hours

OPEN TIME

40-50 minutes

BETWEEN COATS

45-60 minutes

DRYING

Min. 6-8 hours / max. 24 hours

APPLICATION CONDITIONS

10-25°C; RH < 80%; substrate < 4% moisture



COVERAGE

Approximately
70m²
per 7.2 kg pack
(substrate dependent)

APPLICATION



MIXER



ROLLER



SPRAY

PACKAGING



7.2KG
Pack A+B



PROFESSIONAL PERFORMANCE

Engineered for strength, adhesion and durability.



LOW VOC

Safe for installers and the environment.



WATERPROOF

Reliable protection in wet areas.



PREMIUM QUALITY

Developed for the most demanding projects.

MICROSTONE

BY MICROFORCE

microstone.co.uk