



-  WATER BASED
-  HIGH ADHESION
-  SEALS SUBSTRATE
-  LOW VOC
-  INTERIOR EXTERIOR
-  FAST DRYING
-  FOOT TRAFFIC
-  EXCELLENT WORKABILITY

HIDROPRIMER

WATER-BASED PRIMER
& SEALING RESIN

MICROSTONE[®]
BY MICROFORCE

DESCRIPTION

Hidroprimer is a water-based acrylic resin used as the fast-drying primer for Microforce systems on absorbent surfaces — plaster, plasterboard and cement. It also works as a sealer and curing resin for concrete floors, a bonding bridge between concrete and mortar, and as an additive that makes mortars stronger and more flexible.

KEY FEATURES

- Covers approx. 25–50 m² per 5 L
- Fast-drying primer for absorbent substrates
- Sealing and curing resin for concrete floors
- Bonding bridge between concrete and mortar
- Transparent, waterproof and breathable; enhances colour

TECHNICAL INFORMATION

PRODUCT TYPE

Water-based acrylic primer and sealing resin

CONSUMPTION

0.1–0.2 l/m² (as sealer)

TOUCH DRY

Approx. 2 hours

FOOT TRAFFIC

min. 24 hours

VEHICLE TRAFFIC

min. 7 days

FINISH

Satin

PH

7.0–9.0

APPLICATION TEMPERATURE

10–30°C (surface)



HOW IT'S APPLIED

- 1 Prepare** — surface completely clean, free of dust and grease.
- 2 Apply** — by roller or airless in two passes, without pooling.
- 3 As an additive** — up to 10% of the cement weight in mortars.
- 4 Dry** — continue with the next coat once touch dry.

COVERAGE

Approximately
25–50m²
per 5 L
as a sealing resin

APPLICATION



ROLLER



SPRAY



MIXER

PACKAGING



5L
Plastic container



PROFESSIONAL PERFORMANCE

Engineered for strength,
adhesion and durability.



LOW VOC

Safe for installers
and the environment.



WATERPROOF

Reliable protection
in wet areas.



PREMIUM QUALITY

Developed for the most
demanding projects.

MICROSTONE[®]

BY MICROFORCE

microstone.co.uk