



-  **A+B** TWO COMPONENT
-  **HIGH ADHESION**
-  **FLEXIBLE**
-  **WATER BASED**
-  **INTERIOR EXTERIOR**
-  **LOW VOC**
-  **EXCELLENT WORKABILITY**
-  **SEAMLESS FINISH**

LIQUIDO

COMPONENT B FOR
MICROFORCE MICROCEMENT

MICROSTONE®
BY MICROFORCE

DESCRIPTION

Microforce Liquido is the water-based Component B that activates Microforce Thin and Microforce Rustik microcement powders. Mixed 2 parts powder to 1 part Liquido, it gives the finished surface its resistance to abrasion and ageing.

KEY FEATURES

- Component B for Microforce Thin and Rustik
- Water-based
- Excellent resistance to abrasion and ageing
- For floors and façades
- 20 L and 25 L drums

TECHNICAL INFORMATION

PRODUCT TYPE
Water-based liquid component B

MIXING RATIO
2 parts powder : 1 part Liquido

POT LIFE
±60 minutes

OPEN TIME
±15 minutes

TOUCH DRY
2-4 hours

APPLICATION TEMPERATURE
10-30°C

DENSITY
1.09 kg/l at 25°C

PH
8-10



HOW IT'S APPLIED

- 1 Measure** — 1 part Liquido to 2 parts Microforce Thin or Rustik powder.
- 2 Mix** — 5 minutes at low speed to a smooth, lump-free paste.
- 3 Rest** — leave 2 minutes before applying.
- 4 Never add water** — keep the same Liquido ratio throughout the job.

COVERAGE

Mixes with

~43kg

of powder per 20 L drum
~54 kg per 25 L drum

APPLICATION



MIXER



REST 2 MIN



TROWEL

PACKAGING



20L / 25L
Plastic drums



PROFESSIONAL PERFORMANCE

Engineered for strength, adhesion and durability.



LOW VOC

Safe for installers and the environment.



WATERPROOF

Reliable protection in wet areas.



PREMIUM QUALITY

Developed for the most demanding projects.

MICROSTONE®

BY MICROFORCE

microstone.co.uk