



-  PROTECTS
-  SATIN FINISH
-  READY TO USE
-  WATER BASED
-  FAST DRYING
-  FOOT TRAFFIC
-  INTERIOR EXTERIOR
-  LOW VOC

MICROWAX

ACRYLIC FLOOR WAX
FOR MICROCEMENT

MICROSTONE®
BY MICROFORCE

DESCRIPTION

Microwax is an acrylic floor wax — a blend of polymers and waxes — applied over Acryseal to give microcement floors an anti-slip, matt or satin protective layer. It cuts down how often floors need maintaining and suits spray-cleaning and UHS spray-buffing routines.

KEY FEATURES

- Anti-slip effect
- Matt or satin finish
- Reduces maintenance frequency and cost
- Suitable for spray-cleaning and spray-buffing
- Ready to use

TECHNICAL INFORMATION

PRODUCT TYPE
Acrylic polymer and wax emulsion

APPEARANCE
Opaque cream-white liquid

VOC
0.10%

DENSITY
1.023 g/ml

DRY RESIDUE
15 ± 1%

PH
8.5 ± 0.5

BETWEEN COATS
30–60 minutes

MINIMUM TEMPERATURE
10°C



HOW IT'S APPLIED

- 1 Prepare** — apply over Acryseal on a clean, dry floor.
- 2 Apply** — a thin coat with a microfibre mop.
- 3 Second coat** — 30–60 minutes later.
- 4 Maintain** — spray-clean or buff to restore the shine.

COVERAGE

Coverage

Ask us

for a quantity
two thin mop coats

APPLICATION



MOP



TWO COATS



MACHINE

PACKAGING



5L
Plastic bottle



**PROFESSIONAL
PERFORMANCE**
Engineered for strength,
adhesion and durability.



LOW VOC
Safe for installers
and the environment.



WATERPROOF
Reliable protection
in wet areas.



**PREMIUM
QUALITY**
Developed for the most
demanding projects.

MICROSTONE®
BY MICROFORCE

microstone.co.uk