



-  HIGH ADHESION
-  READY TO USE
-  WATER BASED
-  INTERIOR EXTERIOR
-  LOW VOC
-  FAST DRYING
-  OVER TILES
-  EXCELLENT WORKABILITY

PRIMER QUARTZ

TEXTURED ACRYLIC
BONDING PRIMER

MICROSTONE®
BY MICROFORCE

DESCRIPTION

Primer Quartz is a ready-to-use, water-based textured acrylic primer. Its fine, rough structure gives the following coats something to grip, making it a quick way to create a mechanical key before microcement and decorative finishes.

KEY FEATURES

- Covers approx. 25 m² per 5 kg
- Rough texture that anchors following coats
- Ready to use — roller or brush
- Dries in about 1 hour
- Water-based, tools clean with water
- White, fine texture

TECHNICAL INFORMATION

PRODUCT TYPE
Water-based textured acrylic primer

CONSUMPTION
190–200 g/m²

DRYING (1MM, ABSORBENT SUBSTRATE)
Approx. 1 hour

MAXIMUM PARTICLE SIZE
250 µm

DENSITY
1.49 ± 0.07 g/ml

PH
8.0–9.0

APPLICATION TEMPERATURE
5–35°C



HOW IT'S APPLIED

- 1 Prepare** — surface clean, dry and free of dust and grease.
- 2 Stir** — mix the pot well before use.
- 3 Apply** — one coat by roller or brush.
- 4 Dry** — allow to dry fully before the next product.

COVERAGE

Approximately
25m²
per 5 kg pot

APPLICATION



ROLLER



BRUSH



DRY

PACKAGING



5KG
Plastic pot



PROFESSIONAL PERFORMANCE

Engineered for strength,
adhesion and durability.



LOW VOC

Safe for installers
and the environment.



WATERPROOF

Reliable protection
in wet areas.



PREMIUM QUALITY

Developed for the most
demanding projects.

MICROSTONE®

BY MICROFORCE

microstone.co.uk