



- THIN LAYER
- INTERIOR EXTERIOR
- HIGH ADHESION
- FOOT TRAFFIC
- A1 FIRE RATED
- COLOUR OPTIONS
- SEAMLESS FINISH
- EXCELLENT WORKABILITY

COLOUR OPTIONS - 60 SHADES



THIN

TWO-COMPONENT COLOURED
MICROCEMENT · FINE FINISH

MICROSTONE®
BY MICROFORCE

DESCRIPTION

Microforce Thin is a two-component microcement for seamless, joint-free floors and walls. Made in Barcelona from special cement, selected aggregates, resins and pigments, it is mixed 2:1 with Microforce Liquido and hand-trowelled to a fine, smooth finish.

KEY FEATURES

- Covers approx. 25 m² per 15 kg pack in two coats
- Seamless, joint-free finish for floors and walls
- 2-3 mm total system thickness — applies over existing...
- Suitable for pedestrian and vehicle traffic
- Slip resistance Class 1 indoors; Class 2-3 depending on...
- Very low water absorption (0.004 g/cm²)

TECHNICAL INFORMATION

PRODUCT TYPE

Two-component microcement (Component A, powder)

MIXING RATIO

2 parts powder : 1 part Microforce Liquido

THICKNESS

0.1-2 mm finish; 0.5-1 mm max per coat

POT LIFE

±30 minutes

OPEN TIME

±15 minutes

TOUCH DRY

2-4 hours

INTO SERVICE

min. 48 hours (above 20°C)

APPLICATION TEMPERATURE

10-30°C



COVERAGE

Approximately
25m²
per 15 kg pack
in two coats

APPLICATION



TROWEL



MIXER



SEAL

PACKAGING



15KG

Component A - mix
with Liquido



PROFESSIONAL PERFORMANCE

Engineered for strength,
adhesion and durability.



LOW VOC

Safe for installers
and the environment.



WATERPROOF

Reliable protection
in wet areas.



PREMIUM QUALITY

Developed for the most
demanding projects.

MICROSTONE®

BY MICROFORCE

microstone.co.uk