



-  **A+B** TWO COMPONENT
-  **HIGH ADHESION**
-  **HIGH HARDNESS**
-  **WATER BASED**
-  **INTERIOR EXTERIOR**
-  **LOW VOC**
-  **EXCELLENT WORKABILITY**
-  **SEAMLESS FINISH**

LIQUIDO FINISH

COMPONENT B FOR
MICROSTONE THIN-GROUND

MICROSTONE®
BY MICROFORCE

DESCRIPTION

Microstone Liquido Finish is the water-based Component B for Microstone Thin-Ground microquartz. It gives the finished floor its resistance to ageing, abrasion and water — indoors, outdoors and in swimming pools.

KEY FEATURES

- Component B for Microstone Thin-Ground
- Water-based
- Resistant to ageing; excellent abrasion behaviour
- Good water resistance — suitable for pools
- 20 L container — enough for two to three 25 kg bags

TECHNICAL INFORMATION

PRODUCT TYPE

Water-based liquid component B

MIXING RATIO

2.75:1 (8–9 L per 25 kg bag)

POT LIFE

±40 minutes

OPEN TIME

±15 minutes

TOUCH DRY

2 hours

APPLICATION TEMPERATURE

10–30°C

DENSITY

1.09 kg/l at 25°C

PH

8–10



HOW IT'S APPLIED

- 1 Measure** — 1 part Liquido Finish to 3 parts Microstone Thin-Ground.
- 2 Mix** — 5 minutes at low speed to a homogeneous mass.
- 3 Rest** — leave 2 minutes before applying.
- 4 Never add water** — keep the same ratio throughout the job.

COVERAGE

Mixes with

~57kg

of Thin-Ground per 20 L
019 m² Ground or
028 m² Thin coats

APPLICATION



MIXER



REST 2 MIN



TROWEL

PACKAGING



20L
Plastic container



PROFESSIONAL PERFORMANCE

Engineered for strength, adhesion and durability.



LOW VOC

Safe for installers and the environment.



WATERPROOF

Reliable protection in wet areas.



PREMIUM QUALITY

Developed for the most demanding projects.

MICROSTONE®

BY MICROFORCE

microstone.co.uk